



Easy-to-Carry and Easy-to-Use Compact Air Purifier with Mosquito Catcher



City) *3 Effectiveness in a test space of 31 m³ after four weeks of use (one day: 24 hours). (tested by Hiroshima University Graduate School of Advanced Sciences of Matter) *4 Effectiveness in a test space of 41 m³ after 80 min. of use. The effectiveness depends on the odor type, odor intensity, and material

Mosquito Catcher

Capture and Protect from Mosquitoes with 100% Harmless 5 Effective Steps*1 of Mosquito Catcher

Reduce up to 91% of Culex , 73% of Aedes, and 72% of Housefly*2

Effective mechanism based on mosquito behaviour



children

easier

Also, because the mosquitoes are captured on a glue sheet.

mosquitoes, and so cleaning is


the floor remains free of

*2 Result of 24-hour laboratory test in collaboration with the Institute for Medical Research, Malaysia, with Culex quinquefasciatus, Aedes albopictus and aegypti, and Musca domestica.

The efficacy of the mosquito catcher function was tested in a laboratory setting; actual conditions may vary. Continuous usage will improve capture efficacy

Laboratory Test

24hours test was conducted by releasing mosquitoes and flies. Number of captured mosquitoes and flies was counted.



Haze Mode Powerfully Collects Haze Particles and Keeps the Room Air Clean

The air purifier has a Haze Mode. When the air purifier starts in Haze Mode, operation is at maximum airflow for the first 10 minutes, and then switches to a higher airflow for the next 50 minutes. After that, operation repeatedly alternates between lower and higher airflow every 20 minutes. With stronger airflow for the first 60 minutes, a high density of Plasmacluster ions is dispersed into the entire room, which reduces static electricity, making it easy to capture haze particles.



Glue Sheet



Specifications

Models		FP-GM30L-B	FP-FM40L-B	
Color		B (black)	B (black)	
Recommended area	Air purifying*3	21 m ²	30 m ²	
Recommended area for high-density Plasmacluster ions**		16 m ²	23 m ²	
Voltage/frequency (V/Hz)		220-240, 50-60	220-240, 50/60	
Power input (max. / med. / sleep) (W)		53 / 33 / 19	33 / 14 / 3.7-6.2	
Standby power (W)		1.0	1.0	
Airflow (max. / med. / low) (m ³ /hour)		180 / 120 / 78	240 / 150 / 48-90	
Noise level (max. / med. / low) (dB)		47 / 40 / 33	48 / 38 / 20-29	
Filter type	Dust collection	HEPA*5	HEPA*5	
	Deodorization	No	Yes	
	Pre-filter	Yes	Yes	
Filter life	Dust collection	Up to 2 years*6	Up to 2 years*6	
	Deodorizing filter	—	Up to 2 years*6	
Sensor	Dust	No	Yes	
Clean sign indicator	Dust	No	Yes	
Mosquito trap function		Yes	Yes	
Power cord length (m)		2.0	2.0	
Plug type		Type C (2-pin)	Type C (2-pin)	
Dimensions (W x H x D) (mm)		409 x 466 x 259	391 x 540 x 281	
Net weight (kg)		5.0	5.8	
Replacement filter	HEPA filter	FZ-F30HFE	FZ-F40SFE	
Replacement glue sheet		FZ-STS2M (2 Months) *7	FZ-40STS (1 Month) *7	

Safe and Sound Mosquito Capture System

By using non toxic mechanisms which are harmless to people and furniture,

100% harmles

Safe and Sound

protection

the air purifier safely captures mosquitoes even for households with small

Plasmacluster ion purification	Airborne microbes	Airborne mold	Airborne microbes	Airborne viruses
		Dust mite remain allergens	Dust mite feces allergens	Ammonia odor
	Clinging odors	Cigarette odor	Body odor	
Filter purification	Capture and reduction of growth	Airborne microbes	Viruses	Tree pollen
		Dust mite remains	Dust mite feces	
	Capture	Airborne mold	lant pollen	Tree pollen
		🛞 Pet dander	💮 Pet hair	Dust
		Cigarette smoke	📦 Mite dust	Diesel exhaust

approximately 1,2000 inscan be measured per cm³ in the center of the room (at a height of approximately 1,2 meters from the floor) when the product is placed next to a wall and operated at the medium setting. *5 HEPA is defined by the Japan Electrical Manufacturers' Association Standard (JEM1467). The filter removes more than 99,97% of 0.3-micron dust particles. *6 At a smoking rate of five cigarettes per day. *7 Depends on room conditions.

Not all harmful substances in cigarette smoke (e.g., carbon monoxide) can be removed.

* Design and specifications are current as of May 2016, but are subject to change without prior notice * Actual colors may differ slightly from the colors shown in this brochure.





SHARP-ROXY SALES & SERVICE COMPANY (M) SDN. BHD. (8394-W) No.1A, Persiaran Kuala Langat, Section 27, 40400 Shah Alam, Selangor Darul Ehsan. Product Enquiry: 1 800 88 PCI 4 U (72448) (Toll Free) Service Enquiry: Tel: 1 800 888 678 (Toll Free)

SharpPlasmaclusterMalaysia

www.sharp.com.my